



l: Lead Da: Ball Dia. n: Number of circuits K: Stiffness (kgf/μm)

Ca: Basic Dynamix Rating Load (kgf) Coa: Basic Static Rating Load (kgf)

Model No.	Dimensions																
	d	l	Da	D	A	B	L	W	H	X	Y	Z	Q	n	Ca	Coa	K
★ DFI1604-4		4	2.381	30	49	10	100	39	34	4.5	8	4.5	M6	4	625	1254	42
★ DFI1605-4	16	5	3.175	30	49	10	100	39	34	4.5	8	4.2	M6	4	888	1524	43
DFI02004-4		4	2.381	34	57	11	80	45	40	5.5	9.5	5.6	M6	4	693	1584	53
★ DFI02005-4		5	3.175	34	57	11	101	45	40	5.5	9.5	5.5	M6	4	999	1995	53
DFI02504-4	20	4	2.381	40	63	11	80	50	46	5.5	9.5	5.5	M6	4	775	2046	65
★ DFI02505-4		5	3.175	40	63	11	101	51	46	5.5	9.5	5.5	M8	4	1119	2581	66
★ DFI02510-4		10	4.762	46	72	12	145	58	52	6.5	11	6.5	M6	4	1903	3695	67
DFI03204-4	32	4	2.381	46	72	12	80	58	52	6.5	11	6.5	M6	4	868	2640	83
★ DFI03205-4		5	3.175	46	72	12	102	58	52	6.5	11	6.5	M8	4	1264	3403	84
★ DFI03210-4		10	6.35	54	88	15	162	70	62	9	14	8.5	M8	4	3093	6102	86
★ DFI4005-4	40	5	3.175	56	90	15	105	72	64	9	14	8.5	M8	4	1610	5330	98
DFI4010-4		10	6.35	62	104	18	165	82	70	11	17.5	11	M8	4	3910	9520	90
DFI5010-4	50	10	6.35	72	114	18	171	92	82	11	17.5	11	M8	4	4450	12500	117
★ DFI6310-4	63	10	6.35	85	131	22	182	107	95	14	20	13	M8	4	5070	16600	114
★ DFI8010-4	80	10	6.35	105	150	22	182	127	115	14	20	13	M8	4	5620	21300	162

Note: with sign ★ can produce left helix

MVB Power-Star Bearing Industry Co., Ltd.

Tel: +86-592-523 0986 Fax: +86-592-376 1975

Url: www.mvbbearing.com

Email: vivy@mvbbearing.com ; mvbbearing@gmail.com