




**MVB Power-Star Bearing Co.**  
 Url: [www.mvbbearing.com](http://www.mvbbearing.com)  
 Email: [vivy@mvbbearing.com](mailto:vivy@mvbbearing.com)  
[mvbbearing@gmail.com](mailto:mvbbearing@gmail.com)  
 Tel: +86-592-523 0986  
 Fax: +86-592-376 1975



**DEEP GROOVE BALL BEARINGS**

MVB No.	Dimensions (Metric)			Approx. Wgt. (lbs.)	FAG SKF STEYR	Interchange RIV
	d	D	B			
*** 16100	10	28	8	.030	16100	1103a
*** 16101	12	30	8	.057	16101	1938c
* 16002	15	32	8	.060	16002	EL 15
* 16003	17	35	8	.070	16003	EL 17
* 16004	20	42	8	.110	16004	EL 20
* 16005	25	47	8	.140	16005	EL 25
* 16006	30	55	9	.190	16006	EL 30
16007	35	62	9	.250	16007	EL 35
16008	40	68	9	.280	16008	EL 40
16009	45	75	10	.380	16009	ELn 45
16010	50	80	10	.400	16010	ELn 50
16011	55	90	11	.580	16011	ELn 55
16012	60	95	11	.620	16012	ELn 60
16013	65	100	11	.660	16013	ELn 65
16014	70	110	13	.960	16014	ELn 70
16015	75	115	13	1.010	16015	ELn 75
16016	80	125	14	1.310	16016	EL 80
16017	85	130	14	1.380	16017	EL 85
16018	90	140	16	1.870	16018	ELn 90
16019	95	145	16	1.950	16019	ELn 95
16020	100	150	16	2.000	16020	ELn 100
16021	105	160	18	2.640	16021	ELn 105
16022	110	170	19	3.210	16022	ELn 110
16024	120	180	19	3.960	16024	ELn 120
16026	130	200	22	5.920	16026	ELn 130
16028	140	210	22	6.290	16028	ELn 140
16030	150	225	24	7.880	16030	ELn 150
16032	160	240	25	9.500	16032	ELn 160
16034	170	260	28	12.700	16034	ELn 170
16036	180	280	31	16.700	16036	ELn 180
16038	190	290	31	17.400	16038	ELn 190
16040	200	310	34	22.200	16040	ELn 200
16044 M	220	340	37	28.600	16044	-
16048 M	240	360	37	30.600	16048	-
16052 M	260	400	44	46.800	16052	-
16056 M	280	420	44	49.600	16056	-
16060 M	300	460	50	69.900	16060	-
16064 M	320	480	50	73.600	16064	-
16068 M	340	520	57	101.000	16068	-
16072 M	360	540	57	106.000	16072	-
16076 M	380	560	57	111.000	16076	-
16080 M	400	600	63	144.850	16080	-
16084 M	420	620	63	150.800	16084	-
16088 M	440	650	67	176.590	16088	-
16092 M	460	680	71	204.370	16092	-
16096 M	480	700	71	211.650	16096	-
160/500 M	500	720	71	218.920	160/500 M	-

\* Also available with two shields (ZZ). No change in width dimensions.  
 \*\* Also available with two seals (2RS). No change in width dimensions.

NOTE:  
 1.) C/3 and C/4 internal clearances are available on all of the above sizes.