






MVB Power-Star Bearing Co.
 Url: www.mvbbearing.com
 Email: vivy@mvbbearing.com
mvbbearing@gmail.com
 Tel: +86-592-523 0986
 Fax: +86-592-376 1975



Open



Two Shields
ZZ



Two Seals
2RS

DEEP GROOVE BALL BEARINGS - STAINLESS STEEL (440C TYPE)

MVB No.	Dimensions (Metric)			Approx. Wgt. (lbs.)	Interchange	
	d	D	B		FAG	SKF
SS6000	10	26	8	.040	S6000	W6000
SS6001	12	28	8	.050	S6001	W6001
SS6002	15	32	9	.060	S6002	W6002
SS6003	17	35	10	.080	S6003	W6003
SS6004	20	42	12	.140	S6004	W6004
SS6005	25	47	12	.180	S6005	W6005
SS6006	30	55	13	.260	S6006	W6006
SS6007	35	62	14	.330	S6007	W6007
SS6008	40	68	15	.490	S6008	W6008
SS6009	45	75	16	.530	S6009	W6009
SS6010	50	80	16	.580	S6010	W6010
SS6011	55	90	18	.840	S6011	-
SS6012	60	95	18	.910	S6012	-

TWO SHIELDS

SS6000-ZZ	10	26	8	.042	-	W 6000-ZZ
SS6001-ZZ	12	28	8	.049	-	W 6001-ZZ
SS6002-ZZ	15	32	9	.066	-	W 6002-ZZ
SS6003-ZZ	17	35	10	.086	-	W 6003-ZZ
SS6004-ZZ	20	42	12	.152	-	W 6004-ZZ
SS6005-ZZ	25	47	12	.176	-	W 6005-ZZ
SS6006-ZZ	30	55	13	.265	-	W 6006-ZZ
SS6007-ZZ	35	62	14	.353	-	W 6007-ZZ
SS6008-ZZ	40	68	15	.419	-	W 6008-ZZ
SS6009-ZZ	45	75	16	.441	-	W 6009-ZZ
SS6010-ZZ	50	80	16	.573	-	W 6010-ZZ

TWO SEALS


SS6000-2RS	10	26	8	.040	S6000.2RSR	W 6000-2RS1
SS6001-2RS	12	28	8	.050	S6001.2RSR	W 6001-2RS1
SS6002-2RS	15	32	9	.060	S6002.2RSR	W 6002-2RS1
SS6003-2RS	17	35	10	.080	S6003.2RSR	W 6003-2RS1
SS6004-2RS	20	42	12	.140	S6004.2RSR	W 6004-2RS1
SS6005-2RS	25	47	12	.180	S6005.2RSR	W 6005-2RS1
SS6006-2RS	30	55	13	.260	S6006.2RSR	W 6006-2RS1
SS6007-2RS	35	62	14	.330	S6007.2RSR	W 6007-2RS1
SS6008-2RS	40	68	15	.490	S6008.2RSR	W 6008-2RS1
SS6009-2RS	45	75	16	.530	S6009.2RSR	W 6009-2RS1
SS6010-2RS	50	80	16	.580	S6010.2RSR	W 6010-2RS1

NOTE:


- Outer races, inner races and balls are manufactured from 440C or equivalent stainless steel. They are through hardened to a hardness of 55-57 RC.
- The cages are manufactured from 304 or equivalent stainless steel.
- Shields are manufactured from 304 or equivalent stainless steel.
- Seals have a metal core covered with synthetic rubber.




MVB Power-Star Bearing Co.
 Url: www.mvbbearing.com
 Email: vivy@mvbbearing.com
mvbbearing@gmail.com
 Tel: +86-592-523 0986
 Fax: +86-592-376 1975



Open



Two Shields
ZZ



Two Seals
2RS

DEEP GROOVE BALL BEARINGS - STAINLESS STEEL (440C TYPE)

MVB No.	Dimensions (Metric)			Approx. Wgt. (lbs.)	Interchange	
	d	D	B		FAG	SKF
SS6300	10	35	11	.120	S6300	W 6300
SS6301	12	37	12	.140	S6301	W 6301
SS6302	15	42	13	.190	S6302	W 6302
SS6303	17	47	14	.260	S6303	W 6303
SS6304	20	52	15	.320	S6304	W 6304
SS6305	25	62	17	.520	S6305	W 6305
SS6306	30	72	19	.770	S6306	W 6306
SS6307	35	80	21	1.010	S6307	-
SS6308	40	90	23	1.400	S6308	-
SS6309	45	100	25	1.840	S6309	-
SS6310	50	110	27	2.360	S6310	-
SS6311	55	120	29	3.020	S6311	-

TWO SHIELDS

SS6300-ZZ	10	35	11	.117	-	W 6300-ZZ
SS6301-ZZ	12	37	12	.132	-	W 6301-ZZ
SS6302-ZZ	15	42	13	.181	-	W 6302-ZZ
SS6303-ZZ	17	47	14	.264	-	W 6303-ZZ
SS6304-ZZ	20	52	15	.309	-	W 6304-ZZ
SS6305-ZZ	25	62	17	.507	-	W 6305-ZZ

TWO SEALS

SS6300-2RS	10	35	11	.140	S6300.2RSR	W 6300-2RS1
SS6301-2RS	12	37	12	.160	S6301.2RSR	W 6301-2RS1
SS6302-2RS	15	42	13	.210	S6302.2RSR	W 6302-2RS1
SS6303-2RS	17	47	14	.280	S6303.2RSR	W 6303-2RS1
SS6304-2RS	20	52	15	.340	S6304.2RSR	W 6304-2RS1
SS6305-2RS	25	62	17	.540	S6305.2RSR	W 6305-2RS1
SS6306-2RS	30	72	19	.790	S6306.2RSR	-
SS6307-2RS	35	80	21	1.030	S6307.2RSR	-
SS6308-2RS	40	90	23	1.440	S6308.2RSR	-
SS6309-2RS	45	100	25	1.880	S6309.2RSR	-
SS6310-2RS	50	110	27	2.400	S6310.2RSR	-
SS6311-2RS	55	120	29	3.070	S6311.2RSR	-

NOTE:

- 1.) Outer races, inner races and balls are manufactured from 440C or equivalent stainless steel and are through hardened to a hardness of 55-57 RC.
- 2.) The cages are manufactured from 304 or equivalent stainless steel.
- 3.) Shields are manufactured from 304 or equivalent stainless steel.
- 4.) Seals have a metal core covered with synthetic rubber.