




MVB Power-Star Bearing Co.
 Url:www.mvbbearing.com
 Email:vivy@mvbbearing.com
 mvbbearing@gmail.com
 Tel:+86-592-523 0986
 Fax:+86-592-376 1975



DEEP GROOVE BALL BEARINGS - TWO SHIELDS - STAINLESS STEEL - MINIATURE


MVB No.	Dimensions (Metric)			Approx. Wgt. (lbs)	Interchange					
	d	D	B		ADR	ISC	NMB	NTN	RMB	SKF
SS68/1.5-ZZ	1.5	4	2	.0010	-	-	-	-	-	W638/1.5-ZZ
SS682-ZZ	2	5	2.3	.0010	-	682hZZS	SSL-520ZZ	FW682ZZA	-	W638/2-ZZ
SS692-ZZ	2	6	3	.0010	-	692hZZS	SSR-620ZZ	FW692ZZA	-	W639/2-ZZ
SS673-ZZ	3	6	2.5	.0010	-	MR63hZZS	SSL-630ZZ	FW673ZZA	-	-
SS637/3-ZZ	3	6	3	.0010	-	-	-	-	-	W637/3-ZZ
SS683-ZZ	3	7	3	.0010	-	683hZZS	SSL-730ZZ	FW683ZZA	-	W638/3-ZZ
SS619/3-ZZ	3	8	3	.0010	-	-	-	-	-	W619/3-ZZ
SS693-ZZ	3	8	4	.0020	-	693hZZS	SSR-830ZZ	FW693ZZA	-	W639/3-ZZ
SS603-ZZ	3	9	5	.0040	-	-	SSR-930ZZ	FW603ZZA	-	-
SS623-ZZ	3	10	4	.0050	W623ZZ	623hZZS	SSR-1030ZZ	F623ZZ	-	W623ZZ
SS674-ZZ	4	7	2.5	.0010	-	MR74hZZS	SSL-740ZZ	FW674ZZA	-	-
SSAX-4-ZZ	4	9	3.5	.0030	-	-	-	-	-	W628/4-ZZ
SS684-ZZ	4	9	4	.0030	-	684hZZS	SSL-940ZZ	FW684ZZA	-	W638/4-ZZ
SS694-ZZ	4	11	4	.0040	WAY4ZZ	694hZZS	SSR-1140ZZ	F694ZZ	-	W619/4-ZZ
SS604-ZZ	4	12	4	.0040	W604ZZ	604hZZS	SSR-1240ZZ	F604ZZ	-	W604ZZ
SS624-ZZ	4	13	5	.0070	W624ZZ	624hZZ	SSR-1340ZZ	F624ZZ	-	W624ZZ
SS634-ZZ	4	16	5	.0120	W634ZZ	634hZZ	SSR-1640ZZ	F634ZZ	-	-
SS627/5-ZZ	5	11	2.5	.0020	-	-	-	-	-	W627/5-ZZ
SS628/5-ZZ	5	11	4	.0020	-	-	-	-	-	W628/5-ZZ
SS685-ZZ	5	11	5	.0040	-	685hZZS	SSL-1150ZZ	FW685ZZA	-	W638/5-ZZ
SS695-ZZ	5	13	4	.0060	WAY5ZZ	695hZZS	SSR-1350ZZ	F695ZZ	-	W619/3-ZZ
SS605-ZZ	5	14	5	.0060	-	605hZZS	SSR-1450ZZ	F605ZZ	-	-
SS625-ZZ	5	16	5	.0130	W625ZZ	625hZZ	SSR-1650ZZ	F625ZZ	-	W625ZZ
SS635-ZZ	5	19	6	.0200	W635ZZ	635hZZ	SSR-1950ZZ	-	-	W635ZZ
SS676-ZZ	6	10	3	.0030	-	MR106hZZS	SSL-1060ZZ	-	-	W627/6-ZZ
SSMR-126-ZZ	6	12	4	.0020	-	MR126hZZS	SSL-1260ZZ	-	-	-
SSAX-6-ZZ	6	13	4.5	.0050	-	-	-	-	-	-
SS686-ZZ	6	13	5	.0050	-	686hZZS	SSL-1360ZZ	FW686ZZA	-	W628/6-ZZ
SS696-ZZ	6	15	5	.0090	WAY6ZZ	696hZZ	SSR1560ZZ	F696ZZ	-	W619/6-ZZ
SS606-ZZ	6	17	6	.0090	-	606hZZS	SSR-1760ZZ	F606ZZ	-	-
SS626-ZZ	6	19	6	.0229	W626ZZ	-	SSR-1960ZZ	F626ZZ	-	W626ZZ
SS677-ZZ	7	11	3	.0080	-	MR117hZZS	SSL-1170ZZ	-	-	W627/7-ZZ
SS687-ZZ	7	14	5	.0060	-	687hZZS	SSL-1470ZZ	FW687ZZA	-	W628/7-ZZ
SS697-ZZ	7	17	5	.0110	WAY7ZZ	-	-	-	-	W619/7-ZZ
SS607-ZZ	7	19	6	.0200	W607ZZ	-	SSR-1970ZZ	F607ZZ	-	W607ZZ
SS627-ZZ	7	22	7	.0260	W627ZZ	-	SSR-2270ZZ	F627ZZ	-	W627ZZ
SS678-ZZ	8	12	3.5	.0060	-	MR128hZZS	SSL-1280ZZ	-	-	-
SS688-ZZ	8	16	5	.0090	-	688hZZS	SSL-1680ZZ	FW688ZZA	-	W628/8-ZZ
SS638/8-ZZ	8	16	6	.0090	-	-	-	-	-	W638/8-ZZ
SS698-ZZ	8	19	6	.0160	WAY8ZZ	-	-	-	-	W619/8-ZZ
SS608-ZZ	8	22	7	.0330	W608ZZ	-	SSR-2280ZZ	F608ZZ	-	W608ZZ
SS628-ZZ	8	24	8	.0380	-	-	-	-	-	-
SS638-ZZ	8	28	9	.0600	-	-	-	-	-	-
SS689-ZZ	9	17	5	.0150	-	-	SSL-1790ZZ	FW689ZZA	-	W628/9-ZZ
SS699-ZZ	9	20	6	.0170	WAY9ZZ	-	SSL-2090ZZ	F699ZZ	-	W619/9-ZZ
SS609-ZZ	9	24	7	.0330	W609ZZ	-	-	F609ZZ	-	W609ZZ
SS629-ZZ	9	26	8	.0440	-	-	SSR-2690ZZ	F629ZZ	-	W629ZZ

NOTE:

- Outer races, inner races and balls are manufactured from 440C or equivalent stainless steel. They are through hardened to a hardness of 55-57RC.
- The cages are manufactured from 304 or equivalent stainless steel.
- Shields are manufactured from 304 or equivalent stainless steel.



MVB Power-Star Bearing Co.
 Url:www.mvbbearing.com
 Email:vivy@mvbbearing.com
 mvbbearing@gmail.com
 Tel:+86-592-523 0986
 Fax:+86-592-376 1975



DEEP GROOVE BALL BEARINGS - TWO SEALS - STAINLESS STEEL - MINIATURE

MVB No.	Dimensions (Metric)			Approx. Wgt. (lbs)	Interchange		
	d	D	B		ADR	NTN	SKF
SS683-2RS	3	7	3	.0020	-	-	-
SS693-2RS	3	8	4	.0020	-	-	-
SS623-2RS	3	10	4	.0040	-	F623LLU	-
SS684-2RS	4	9	4	.0030	-	-	-
SS694-2RS	4	11	4	.0030	-	-	-
SS624-2RS	4	13	5	.0090	-	F624LLU	W624-2RS1
SS634-2RS	4	16	5	.0110	-	F634LLU	-
SS685-2RS	5	11	5	.0040	-	-	-
SS695-2RS	5	13	4	.0060	-	-	-
SS605-2RS	5	14	5	.0060	-	F605LLU	-
SS625-2RS	5	16	5	.0130	-	F625LLU	W625-2RS1
SS635-2RS	5	19	6	.0200	-	F635LLU	-
SS686-2RS	6	13	5	.0050	-	-	-
SS696-2RS	6	15	5	.0090	-	-	-
SS606-2RS	6	17	6	.0060	-	F606LLU	-
SS626-2RS	6	19	6	.0220	-	F626LLU	W626-2RS1
SS687-2RS	7	14	5	.0060	-	-	-
SS697-2RS	7	17	5	.0110	-	-	-
SS607-2RS	7	19	6	.0200	-	F607LLU	W607-2RS1
SS627-2RS	7	22	7	.0260	-	F627LLU	-
SS688-2RS	8	16	5	.0080	-	-	-
SS638/8-2RS	8	16	6	.0090	-	-	-
SS698-2RS	8	19	6	.0160	-	-	W619/8-2RS1
SS608-2RS	8	22	7	.0330	-	F608LLU	W608-2RS1
SS628-2RS	8	24	8	.0420	-	F628LLU	-
SS689-2RS	9	17	5	.0090	-	-	-
SS699-2RS	9	20	6	.0170	-	-	-
SS609-2RS	9	24	7	.0330	-	F609LLU	-
SS629-2RS	9	26	8	.0440	-	F629LLU	-

NOTE:

- 1.) Outer races, inner races and balls are manufactured from 440C or equivalent stainless steel. They are through hardened to a hardness of 55-57RC.
- 2.) The cages are manufactured from 304 or equivalent stainless steel.
- 3.) Seals have a metal core covered with synthetic rubber.