


OUC200 (Normal Duty)
Spherical O.D.



OCUC200 (Normal Duty)
Cylindrical O.D.



OUC200G (Normal Duty)
Relubricatable Type



SL TYPE SEAL



TJ TYPE SEAL



LJ TYPE SEAL

MVB Bearings No.	Shaft Dia d		Dimensions (in) / (mm)								Basic Dynamic Load Rating (KN)	Basic Static Load Rating (KN)	Weight (kg)	
	(in)	(mm)	D	Bi	Be	n	m	G	ds (in) / (mm)	F				
OUCW201-8	1/2											7.36	4.48	0.12
OUCW202-9	9/16		1.5748	1.0787	0.5512	0.4528	0.6260	0.1654	10-32UNF	0.1614	0.11			
OUCW202-10	5/8										0.11			
OUCW203-11	11/16										0.10			
OUCW201		12									0.12			
OUCW202		15	40	27.4	14	11.5	15.9	4.2	M5x0.8	4.1	0.11			
OUCW203		17									0.10			
OUC201-8	1/2										9.88	6.2	0.2	
OUC202-9	9/16		1.8504	1.2205	0.6693	0.5000	0.7205	0.1969	1/4-28UNF	0.1693				0.19
OUC202-10	5/8													0.19
OUC203-11	11/16													0.18
OUC204-12	3/4													0.16
OUC201		12									0.21			
OUC202		15	47	31	17	12.7	18.3	5	M6x1	4.3	0.19			
OUC203		17									0.18			
OUC204		20									0.16			
OUC205-13	13/16										10.78	6.98	0.22	
OUC205-14	7/8		2.0472	1.3425	0.6693	0.5630	0.7795	0.1969	1/4-28UNF	0.1575				0.2
OUC205-15	15/16													0.19
OUC205-16	1													0.19
OUC205		25	52	34.1	17	14.3	19.8	5	M6x1	4				0.19
OUC206-17	1-1/16										14.97	10.04	0.36	
OUC206-18	1-1/8		2.4409	1.5000	0.7480	0.6260	0.8740	0.2165	1/4-28UNF	0.2087				0.34
OUC206-19	1-3/16													0.32
OUC206-20	1-1/4													0.31
OUC206		30	62	38.1	19	15.9	22.2	5.5	M6x1	5.3				0.31
OUC207-20	1-1/4										19.75	13.67	0.52	
OUC207-21	1-5/16		2.8346	1.6890	0.7874	0.6890	1	0.2362	5/16-24UNF	0.2283				0.5
OUC207-22	1-3/8													0.48
OUC207-23	1-7/16													0.46
OUC207		35	72	42.9	20	17.5	25.4	6	M8x1	5.8				0.46
OUC208-24	1-1/2										22.71	15.94	0.68	
OUC208-25	1-9/16		3.1496	1.9370	0.8268	0.7480	1.1890	0.3150	5/16-24UNF	0.2441				0.64
OUC208		40	80	49.2	21	19	30.2	8	M8x1	6.2				0.63
OUC209-26	1-5/8													0.78
OUC209-27	1-11/16		3.3465	1.9370	0.8661	0.7480	1.1890	0.3150	5/16-24UNF	0.2559				0.74
OUC209-28	1-3/4										0.7			
OUC209		45	85	49.2	22	19	30.2	8	M8x1	6.5	0.68			
OUC210-29	1-13/16										26.98	19.84	0.85	
OUC210-30	1-7/8		3.5433	2.0315	0.9055	0.7480	1.2835	0.3543	3/8-24UNF	0.2756				0.8
OUC210-31	1-15/16													0.78
OUC210-32	2													0.78
OUC210		50	90	51.6	23	19	32.6	9	M10x1.25	7				0.78
OUC211-32	2										33.37	25.11	1.22	
OUC211-33	2-1/16		3.9370	2.1890	0.9843	0.8740	1.3150	0.3543	3/8-24UNF	0.2913				1.1
OUC211-34	2-1/8													1.05
OUC211-35	2-3/16													1.07
OUC211		55	100	55.6	25	22.2	33.4	9	M10x1.25	7.4				1.07
OUC212-36	2-1/4										36.74	27.97	1.65	
OUC212-37	2-5/16		4.3307	2.5630	1.0630	1.0000	1.5630	0.4134	3/8-24UNF	0.2992				1.52
OUC212-38	2-3/8													1.51
OUC212-39	2-7/16													1.42
OUC212		60	110	65.1	27	25.4	39.7	10.5	M10x1.25	7.6				1.42
OUC213-39	2-1/2										44.01	34.18	1.96	
OUC213-40	2-9/16		4.7244	2.5630	1.1024	1.0000	1.5630	0.4724	3/8-24UNF	0.3346				1.94
OUC213		65	120	65.1	28	25.4	39.7	12	M10x1.25	8.5				1.86
OUC214-42	2-5/8													2.28
OUC214-43	2-11/16		4.9213	2.9370	1.1811	1.1890	1.7480	0.4724	7/16-20UNF	0.3504				2.28
OUC214-44	2-3/4										2.06			
OUC214		70	125	74.6	30	30.2	44.4	12	M12x1.5	8.9	2.18			
OUC215-45	2-13/16										50.85	41.26	2.3	
OUC215-46	2-7/8		5.1181	3.0630	1.1811	1.3110	1.7520	0.4724	7/16-20UNF	0.3622				2.3
OUC215-47	2-15/16													2.3
OUC215-48	3													2.13
OUC215		75	130	77.8	30	33.3	44.5	12	M12x1.5	9.2				2.21
OUC216-50	3-1/8										55.04	45.09	2.9	
OUC216		80	5.5118	3.2520	1.2992	1.3110	1.9409	0.5512	7/16-20UNF	0.3740				2.82
			140	82.6	33	33.3	49.3	14	M12x1.5	9.5				
OUC217-52	3-1/4		5.9055	3.3740	1.3780	1.3425	2.0315	0.5512	7/16-20UNF	0.4370				3.56
OUC217		85	150	85.7	35	34.1	51.6	14	M12x1.5	11.1				3.46
OUC218-56	3-1/2										73.83	60.76	4.62	
OUC218		90	6.2992	3.7795	1.4567	1.5630	2.2165	0.5512	1/2-20UNF	0.4646				4.62
			160	96	37	39.7	56.3	14	M12x1.5	11.8				4.53