


SA200 & CSA200 Series

Ball Bearing Inserts 外球面轴承




Mounted Ball Bearing Units


Narrow Inner Race, Eccentric Collar Locking, Light Duty



SA200 Spherical O.D.



SA200G
Relubricatable Type



CSA200 Cylindrical O.D.



J TYPE SEAL



H TYPE SEAL

www.mvbbearing.com

MVB Bearing No.		Shaft Dia d		Dimensions inch mm										Basic Load Ratings (KN)		Weight (kg)			
Spherical Out Ring	Cylindrical Out Ring	(in)	(mm)	Bi	D	B	r	n	m	L	d1	B3	G	ds (in.UNF)/(mm)	Dynamic Cr		Static Cor		
SA201-8	CSA201-8	1/2																0.14	
SA202-9	CSA202-9	9/16		0.4724	1.5748	0.7520	0.0315	0.2362	0.5157	1.1260	1.1260	0.5315	0.1969	10-32UNF	7.36	4.48	0.13		
SA202-10	CSA202-10	5/8																	0.12
SA203-11	CSA203-11	11/16																	0.12
SA201	CSA201		12																0.11
SA202	CSA202		15	12	40	19.1	0.8	6	13.1	28.6	28.6	13.5	5	M5x0.8			0.1		
SA203	CSA203		17														0.09		
SA204-12	CSA204-12	3/4		0.5512	1.8504	0.8465	0.0591	0.2756	0.5709	1.2205	1.3110	0.5315	0.1969	1/4-28UNF	9.88	6.2	0.15		
SA204	CSA204		20	14	47	21.5	1.5	7	14.5	31	33.3	13.5	5	M6x1					0.16
SA205-14	CSA205-14	7/8		0.5906	2.0472	0.8465	0.0591	0.2953	0.5512	1.2205	1.5000	0.5315	0.1969	1/4-28UNF	10.78	6.98	0.21		
SA205-15	CSA205-15	15/16																	0.19
SA205-16	CSA205-16	1																	0.18
SA205	CSA205		25	15	52	21.5	1.5	7.5	14	31	38.1	13.5	5	M6x1					0.18
SA206-17	CSA206-17	1-1/16															0.34		
SA206-18	CSA206-18	1-1/8		0.6299	2.4409	0.9370	0.0591	0.3150	0.6220	1.4055	1.7520	0.6260	0.2362	5/16-24UNF	14.97	10.04	0.32		
SA206-19	CSA206-19	1-3/16																	0.3
SA206-20	CSA206-20	1-1/4																	0.29
SA206	CSA206		30	16	62	23.8	1.5	8	15.8	35.7	44.5	15.9	6	M8x1					0.3
SA207-20	CSA207-20	1-1/4															0.55		
SA207-21	CSA207-21	1-5/16		0.6693	2.8346	1.0000	0.0787	0.3346	0.6654	1.5315	2.1890	0.6890	0.2559	5/16-24UNF	19.75	13.67	0.53		
SA207-22	CSA207-22	1-3/8																	0.5
SA207-23	CSA207-23	1-7/16																	0.47
SA207	CSA207		35	17	72	25.4	2	8.5	16.9	38.9	55.6	17.5	6.5	M8x1					0.5
SA208-24	CSA208-24	1-1/2		0.7087	3.1496	1.1890	0.0787	0.3543	0.8346	1.7205	2.3740	0.7205	0.2559	5/16-24UNF	22.71	15.94	0.67		
SA208-25	CSA208-25	1-9/16																	0.65
SA208	CSA208		40	18	80	30.2	2	9	21.2	43.7	60.3	18.3	6.5	M8x1					0.63
SA209-26	CSA209-26	1-5/8															0.74		
SA209-27	CSA209-27	1-11/16		0.7480	3.3465	1.1890	0.0787	0.3740	0.8150	1.7205	2.5000	0.7205	0.2559	5/16-24UNF	24.36	17.71	0.72		
SA209-28	CSA209-28	1-3/4																	0.67
SA209	CSA209		45	19	85	30.2	2	9.5	20.7	43.7	63.5	18.3	6.5	M8x1					0.66
SA210-29	CSA210-29	1-13/16																	0.9
SA210-30	CSA210-30	1-7/8		0.7874	3.5433	1.1890	0.0787	0.3937	0.7953	1.7205	2.7520	0.7205	0.2559	5/16-24UNF	26.98	19.84	0.86		
SA210-31	CSA210-31	1-15/16																	0.83
SA210-32	CSA210-32	2																	0.79
SA210	CSA210		50	20	90	30.2	2	10	20.2	43.7	69.9	18.3	6.5	M8x1					0.8
SA211-32	CSA211-32	2															0.95		
SA211-33	CSA211-33	2-1/16		0.8268	3.9370	1.2795	0.0984	0.4724	0.8661	1.9055	3.0000	0.8150	0.3150	5/16-24UNF	33.37	25.11	0.91		
SA211-34	CSA211-34	2-1/8																	0.86
SA211-35	CSA211-35	2-3/16																	0.81
SA211	CSA211		55	21	100	32.5	2.5	12	22	48.4	76.2	20.7	8	M8x1					0.77
SA212-36	CSA212-36	2-1/4															1		
SA212-37	CSA212-37	2-5/16		0.8661	4.3307	1.4606	0.0984	0.4724	1.0276	2.0906	3.3150	0.8780	0.3150	3/8-24UNF	36.74	27.97			
SA212-38	CSA212-38	2-3/8																	
SA212-39	CSA212-39	2-7/16																	
SA212	CSA212		60	22	110	37.1	2.5	12	26.1	53.1	84.2	22.3	8	M10x1.25					0.98
																		0.99	