


# Self-aligning Ball Bearings


## 调心球轴承

**XMVB<sup>®</sup>**  
**BEARINGS**

XMVB Power-Star Bearing Co.  
Url: [www.mvbbearing.com](http://www.mvbbearing.com)  
Email: [vivy@mvbbearing.com](mailto:vivy@mvbbearing.com)  
[mvbbearing@gmail.com](mailto:mvbbearing@gmail.com)  
Tel: +86-592-523 0986  
Fax: +86-592-376 1975



Cylindrical Bore  
Open



Tapered Bore - 1:12  
Open

### SELF-ALIGNING BALL BEARINGS

No.	Dimensions (Metric)			Approx. Wgt. (lbs.)	Interchange						
	d	D	B		FAG	FAF	FED	MRC	SKF	STEYR	
2300	10	35	17	.190	-	-	2300 SA	-	-	-	
2301	12	37	17	.220	-	L-6301	2301 SA	2301	2301	-	
2302	15	42	17	.260	2302	L-6302-2	2302 SA	2302	2302	-	
2303	17	47	19	.350	2303	-	2303 SA	2303	2303	2303	
2304	20	52	21	.470	2304	-	2304 SA	2304	2304	2304 E/TG	
2305	2305K	25	62	24	.740	2305 TV	-	2305 SA	2305	2305	2305 E/TG
2306	2306K	30	72	27	1.100	2306 TV	-	2306 SA	2306	2306	2306
2307	2307K	35	80	31	1.490	2307 TV	L-6307	2307 SA	2307 E	2307 E	2307 E/TG
2308	2308K	40	90	33	2.040	2308 TV	L-6308	2308 SA	2308 E	2308 E	2308 E/TG
2309	2309K	45	100	36	2.710	2309 TV	L-6309	2309 SA	2309 E	2309 E	2309 E/TG
2310	2310K	50	110	40	3.620	2310 TV	L-6310	2310 SA	2310	2310	2310
2311	2311K	55	120	43	4.630	2311 TV	L-6311	2311 SA	2311	2311	2311
2312	2312K	60	130	46	5.730	2312 TV	L-6312	2312 SA	2312	2312	2312
2313	2313K	65	140	48	7.120	2313	-	2313 SA	2313	2313	2313
2314	2314K	70	150	51	9.460	2314	L-6314	2314 SA	2314	2314	2314
2315	2315K	75	160	55	11.440	2315	-	2315 SA	2315	2315	2315
2316	2316K	80	170	58	14.850	2316 M	-	2316 SA	2316	2316	2316
2317 M	2317 MK	85	180	60	17.050	2317 M	L-6317	2317 SA	2317	2317	2317 M
2318 M	2318 MK	90	190	64	20.460	2318 M	-	2318 SA	2318	2318M	2318 M
2319 M	2319 MK	95	200	67	23.760	2319 M	-	2319 SA	2319	2319M	-
2320 M	2320 MK	100	215	73	30.030	2320 M	-	2320 SA	2320	2320M	-
2321 M	2321 MK	105	225	77	35.890	2321	-	2321 SA	-	-	-
2322 M	2322 MK	110	240	80	43.420	2322	-	2322 SA	2322	2322	-



**NOTE:**

- 1.) 2304 thru 2316 also available with machined bronze cage - "M" suffix.
- 2.) Above sizes also available in C/2, C/3, C/4 and C/5 internal clearances.
- 3.) Allowable misalignment 4°.

# Self-aligning Ball Bearings 调心球轴承

**XMVB**  
**BEARINGS**

XMVB Power-Star Bearing Co.  
Url: [www.mvbbearing.com](http://www.mvbbearing.com)  
Email: [vivy@mvbbearing.com](mailto:vivy@mvbbearing.com)  
[mvbbearing@gmail.com](mailto:mvbbearing@gmail.com)  
Tel: +86-592-523 0986  
Fax: +86-592-376 1975



## SELF-ALIGNING BALL BEARINGS - TWO SEALS

2300-2RS  
2301-2RS  
2302-2RS  
2303-2RS  
2304-2RS

2305-2RS  
2306-2RS  
2307-2RS  
2308-2RS  
2309-2RS

2310-2RS  
2311-2RS  
2312-2RS  
2313-2RS  
2314-2RS

## TAPERED BORE - TWO SEALS

2304-K 2RS  
2305-K 2RS  
2306-K 2RS  
2307-K 2RS  
2308-K 2RS

2309-K 2RS  
2310-K 2RS  
2311-K 2RS  
2312-K 2RS  
2313-K 2RS

2314-K 2RS