



MVB Bearing Unit No.	Shaft Dia.		Dimensions (in./mm)											Bolt Used		Bearing No.	Housing No.	Weight Lbs./kg
	d		h	a	e	b	S2	S1	g	w	Bi	n	K	Used				
	in.	(mm)												(mm)	(in.)			
SAP201-08 SAP201	1/2	12	1 3/16 30.2	5 127	3 3/4 95.3	1 1/2 38.1	3/4 19	1/2 12.7	9/16 14	2 7/16 62	1.0070 28.6	0.2113 6	1.0070 28.6	M10	3/8	SA201-8 SA201	P 203	1.41 0.64
SAP202-9 SAP202-10 SAP202	9/16 5/8	15	1 3/16 30.2	5 127	3 3/4 95.3	1 1/2 38.1	3/4 19	1/2 12.7	9/16 14	2 7/16 62	1.0070 28.6	0.2113 6	1.0070 28.6	M10	3/8	SA202-9 SA202-10 SA202	P 203	1.39 0.63
SAP203-11 SAP203	11/16	17	1 3/16 30.2	5 127	3 3/4 95.3	1 1/2 38.1	3/4 19	1/2 12.7	9/16 14	2 7/16 62	1.0070 28.6	0.2113 6	1.0070 28.6	M10	3/8	SA203-11 SA203	P 203	1.36 0.62
SAP204-12 SAP204	3/4	20	1 5/16 33.3	5 127	3 3/4 95.3	1 1/2 38.1	3/4 19	1/2 12.7	9/16 14	2 17/32 64.3	1.0915 31	0.2465 7	1.1725 33.3	M10	3/8	SA204-12 SA204	P 204	1.43 0.65
SAP205-13 SAP205-14 SAP205-15 SAP205-16 SAP205	13/16 7/8 15/16 1	25	1 7/16 36.5	5 1/2 140	4 1/8 105	1 1/2 38.1	3/4 19	1/2 12.7	19/32 15	2 25/32 70.6	1.0915 31	0.2641 7.5	1.3415 38.1	M10	3/8	SA205-13 SA205-14 SA205-15 SA205-16 SA205	P 205	1.81 0.82
SAP206-17 SAP206-18 SAP206-19 SAP206-20 SAP206	1-1/16 1-1/8 1-3/16 1-1/4	30	1 11/16 42.9	6 1/2 165	4 3/4 120.7	1 7/8 47.6	25/32 20	21/32 16.7	21/32 16.7	3 5/16 84.1	1.2570 35.7	0.2817 8	1.5669 44.5	M14	1/2	SA206-17 SA206-18 SA206-19 SA206-20 SA206	P 206	2.89 1.31
SAP207-20 SAP207-21 SAP207-22 SAP207-23 SAP207	1-1/4 1-5/16 1-3/8 1-7/16	35	1 7/8 47.6	6 9/16 167	5 127	1 7/8 47.6	25/32 20	21/32 16.7	45/64 18	3 21/32 92.9	1.5315 38.9	0.3346 8.5	2.1890 55.6	M14	1/2	SA207-20 SA207-21 SA207-22 SA207-23 SA207	P 207	3.57 1.62
SAP208-24 SAP208-25 SAP208	1-1/2 1-9/16	40	1 15/16 49.2	7 1/4 184	5 13/32 137.3	2 1/8 54	25/32 20	21/32 16.7	45/64 18	3 27/32 97.6	1.7205 43.7	0.3543 9	2.3740 60.3	M14	1/2	SA208-24 SA208-25 SA208	P 208	4.50 2.04
SAP209-26 SAP209-27 SAP209-28 SAP209	1-5/8 1-11/16 1-3/4	45	2 1/8 54.0	7 15/32 190	5 3/4 146	2 1/8 54	25/32 20	21/32 16.7	25/32 20	4 3/16 106.4	1.7205 43.7	0.3740 9.5	2.5000 63.5	M14	1/2	SA209-26 SA209-27 SA209-28 SA209	P 209	5.25 2.38
SAP210-29 SAP210-30 SAP210-31 SAP210-32 SAP210	1-13/16 1-7/8 1-15/16 2	50	2 1/4 57.2	8 1/8 206	6 1/4 159	2 3/8 60.3	29/32 23	25/32 19.8	53/64 21	4 7/16 112.7	1.7205 43.7	0.3937 10	2.7520 69.9	M16	5/8	SA210-29 SA210-30 SA210-31 SA210-32 SA210	P 210	6.11 2.77
SAP211-32 SAP211-33 SAP211-34 SAP211-35 SAP211	2 2-1/16 2-1/8 2-3/16	55	2 1/2 63.5	8 5/8 219	6 23/32 170.7	2 3/8 60.3	29/32 23	25/32 19.8	29/32 23	4 29/32 124.6	1.9055 48.4	0.4724 12	3.0000 76.2	M16	5/8	SA211-32 SA211-33 SA211-34 SA211-35 SA211	P 211	7.63 3.46
SAP212-36 SAP212-37 SAP212-38 SAP212-39 SAP212	2-1/4 2-5/16 2-3/8 2-7/16	60	2 3/4 69.8	9 1/2 241	7 1/4 184.2	2 3/4 70	29/32 23	25/32 19.8	63/64 25	5 7/16 138.1	2.0906 53.1	0.4724 12	3.3150 84.2	M16	5/8	SA212-36 SA212-37 SA212-38 SA212-39 SA212	P 212	10.67 4.84

NOTE: 1. Grease Fittings available at 90° and 45° positions.