


SB200 Spherical O.D.



CSB200 Cylindrical O.D.



SB200G  
Relubricatable Type



J TYPE SEAL  
H TYPE SEAL

www.mvbbearing.com

MVB Bearing No.		Shaft Dia d		Dimensions(mm)								Basic Load Ratings (KN)		Weight (kg)
Spherical Out Ring	Cylindrical Out Ring	(in)	(mm)	Be	D	Bi	r	n	m	G	ds (in.UNF)/(mm)	Dynamic Cr	Static Cor	
SB201-8	CSB201-8	1/2												0.09
SB202-9	CSB202-9	9/16		0.4724	1.5748	0.8661	0.0394	0.2362	0.6299	0.1772	10-32UNF			0.08
SB202-10	CSB202-10	5/8												0.08
SB203-11	CSB203-11	11/16										7.36	4.48	0.07
SB201	CSB201		12											0.09
SB202	CSB202		15	12	40	22	1	6	16	4.5	M5x0.8			0.08
SB203	CSB203		17											0.07
SB204-12	CSB204-12	3/4		0.5512	1.8504	0.9843	0.0591	0.2756	0.7087	0.1772	1/4-28UNF			0.12
SB204	CSB204		20	14	47	25	1.5	7	18	4.5	M6x1	9.88	6.2	
SB205-14	CSB205-14	7/8		0.5906	2.0472	1.0630	0.0591	0.2953	0.7677	0.1969	1/4-28UNF			0.18
SB205-15	CSB205-15	15/16										10.78	6.98	0.17
SB205-16	CSB205-16	1												0.16
SB205	CSB205		25	15	52	27	1.5	7.5	19.5	5	M6x1			0.17
SB206-17	CSB206-17	1-1/16												0.28
SB206-18	CSB206-18	1-1/8		0.6299	2.4409	1.1811	0.0591	0.3150	0.8661	0.2165	5/16-24UNF			0.26
SB206-19	CSB206-19	1-3/16										14.97	10.04	0.25
SB206-20	CSB206-20	1-1/4												0.23
SB206	CSB206		30	16	62	30	1.5	8	22	5.5	M8x1			0.25
SB207-20	CSB207-20	1-1/4												0.41
SB207-21	CSB207-21	1-5/16		0.6693	2.8346	1.2598	0.0787	0.3346	0.9252	0.2362	5/16-24UNF			0.39
SB207-22	CSB207-22	1-3/8										19.75	13.67	0.37
SB207-23	CSB207-23	1-7/16												0.35
SB207	CSB207		35	17	72	32	2	8.5	23.5	6	M8x1			0.37
SB208-24	CSB208-24	1-1/2		0.7087	3.1496	1.3386	0.0787	0.3543	0.9843	0.3150	5/16-24UNF			0.48
SB208-25	CSB208-25	1-9/16										22.71	15.94	0.45
SB208	CSB208		40	18	80	34	2	9	25	8	M8x1			0.45
SB209-26	CSB209-26	1-5/8												0.8
SB209-27	CSB209-27	1-11/16		0.7480	3.3465	1.6220	0.0787	0.4016	1.2205	0.3150	5/16-24UNF			0.8
SB209-28	CSB209-28	1-3/4										24.36	17.71	
SB209	CSB209		45	19	85	41.2	2	10.2	31	8	M8x1			
SB210-29	CSB210-29	1-13/16												0.87
SB210-30	CSB210-30	1-7/8		0.7874	3.5433	1.7126	0.0787	0.4291	1.2835	0.3543	5/16-24UNF			0.87
SB210-31	CSB210-31	1-15/16										26.98	19.84	
SB210-32	CSB210-32	2												
SB210	CSB210		50	20	90	43.5	2	10.9	32.6	9	M8x1			
SB211-32	CSB211-32	2												1.1
SB211-33	CSB211-33	2-1/16		0.8268	3.9370	1.7835	0.0984	0.4646	1.3189	0.3937	5/16-24UNF			1.1
SB211-34	CSB211-34	2-1/8										33.37	25.11	
SB211-35	CSB211-35	2-3/16												
SB211	CSB211		55	21	100	45.3	2.5	11.8	33.5	10	M8x1			
SB212-36	CSB212-36	2-1/4												1.3
SB212-37	CSB212-37	2-5/16		0.8661	4.3307	2.1142	0.0984	0.5866	1.5276	0.3937	3/8-24UNF			1.3
SB212-38	CSB212-38	2-3/8										36.74	27.97	
SB212-39	CSB212-39	2-7/16												
SB212	CSB212		60	22	110	53.7	2.5	14.9	38.8	10	M10x1.25			