



SBPF200

SAPF200

MVB Bearing Unit No.		Shaft Dia d		Dimensions inch mm							Bolt Size (mm)	Bearing No.		Housing No.	Weight (kg)	
		(in)	(mm)	a	e	m	t	s	Bi	B					SBPF	SAPF
SBPF201-8	SAPF201-8	1/2										SA201-8	SB201-8			
SBPF202-9	SAPF202-9	9/16		3.1890	2.5000	0.5512	0.1575	0.2756	0.8661	1.1260	1/4	SA202-9	SB202-9			
SBPF202-10	SAPF202-10	5/8										SA202-10	SB202-10			
SBPF203-11	SAPF203-11	11/16										SA203-11	SB203-11	PF203	0.23	0.27
SBPF201	SAPF201	12										SA201	SB201			
SBPF202	SAPF202	15		81	63.5	14	4	7	22	28.6	M6	SA202	SB202			
SBPF203	SAPF203	17										SA203	SB203			
SBPF204-12	SAPF204-12	3/4		3.5433	2.7953	0.6614	0.1575	0.3543	0.9843	1.2205	5/16	SA204-12	SB204-12	PF204	0.26	0.29
SBPF204	SAPF204	20		90	71	16.8	4	9	25	31	M8	SA204	SB204			
SBPF205-13	SAPF205-13	13/16										SA205-13	SB205-13			
SBPF205-14	SAPF205-14	7/8		3.7402	2.9921	0.7362	0.1575	0.3543	1.0630	1.2402	5/16	SA205-14	SB205-14			
SBPF205-15	SAPF205-15	15/16										SA205-15	SB205-15	PF205	0.35	0.39
SBPF205-16	SAPF205-16	1										SA205-16	SB205-16			
SBPF205	SAPF205	25		95	76	18.7	4	9	27	31.5	M8	SA205	SB205			
SBPF206-17	SAPF206-17	1-1/16										SA206-17	SB206-17			
SBPF206-18	SAPF206-18	1-1/8		4.4488	3.5433	0.7677	0.1969	0.4331	1.1811	1.4055	3/8	SA206-18	SB206-18			
SBPF206-19	SAPF206-19	1-3/16										SA206-19	SB206-19	PF206	0.46	0.50
SBPF206-20	SAPF206-20	1-1/4										SA206-20	SB206-20			
SBPF206	SAPF206	30		113	90	19.5	5	11	30	35.7	M10	SA206	SB206			
SBPF207-20	SAPF207-20	1-1/4										SA207-20	SB207-20			
SBPF207-21	SAPF207-21	1-5/16		4.8031	3.9370	0.7480	0.1969	0.4331	1.2598	1.5315	3/8	SA207-21	SB207-21			
SBPF207-22	SAPF207-22	1-3/8										SA207-22	SB207-22	PF207	0.73	0.80
SBPF207-23	SAPF207-23	1-7/16										SA207-23	SB207-23			
SBPF207	SAPF207	35		122	100	19	5	11	32	38.9	M10	SA207	SB207			
SBPF208-24	SAPF208-24	1-1/2		5.8268	4.6850	0.8898	0.2362	0.5315	1.3386	1.7205	1/2	SA208-24	SB208-24			
SBPF208-25	SAPF208-25	1-9/16										SA208-25	SB208-25	PF208	0.94	1.01
SBPF208	SAPF208	40		148	119	22.6	6	13.5	34	43.7	M12	SA208	SB208			
SBPF209-26	SAPF209-26	1-5/8										SA209-26	SB209-26			
SBPF209-27	SAPF209-27	1-11/16		5.8661	4.7441	0.8661	0.2362	0.5315	1.6220	1.7205	1/2	SA209-27	SB209-27	PF209	1.44	1.56
SBPF209-28	SAPF209-28	1-3/4										SA209-28	SB209-28			
SBPF209	SAPF209	45		149	120.5	22	6	13.5	41.2	43.7	M12	SA209	SB209			
SBPF210-29	SAPF210-29	1-13/16										SA210-29	SB210-29			
SBPF210-30	SAPF210-30	1-7/8		6.1811	5.0000	1.0453	0.3150	0.5315	1.7126	1.7205	1/2	SA210-30	SB210-30			
SBPF210-31	SAPF210-31	1-15/16										SA210-31	SB210-31	PF210	1.81	1.92
SBPF210-32	SAPF210-32	2										SA210-32	SB210-32			
SBPF210	SAPF210	50		157	127	26.55	8	13.5	43.5	43.7	M12	SA210	SB210			
SBPF211-32	SAPF211-32	2										SA211-32	SB211-32			
SBPF211-33	SAPF211-33	2-1/16		6.6142	5.4331	1.0039	0.3150	0.5315	1.7835	1.9055	1/2	SA211-33	SB211-33	PF211	2.01	2.19
SBPF211-34	SAPF211-34	2-1/8										SA211-34	SB211-34			
SBPF211-35	SAPF211-35	2-3/16										SA211-35	SB211-35			
SBPF211	SAPF211	55		168	138	25.5	8	13.5	45.3	48.4	M12	SA211	SB211			
SBPF212-36	SAPF212-36	2-1/4										SA212-36	SB212-36			
SBPF212-37	SAPF212-37	2-5/16		6.9685	5.8268	1.1024	0.3150	0.5315	2.1142	2.0906	1/2	SA212-37	SB212-37			
SBPF212-38	SAPF212-38	2-3/8										SA212-38	SB212-38	PF212	2.31	2.56
SBPF212-39	SAPF212-39	2-7/16										SA212-39	SB212-39			
SBPF212	SAPF212	60		177	148	28	8	13.5	53.7	53.1	M12	SA212	SB212			

Note: PF208-212 with 4 bolt holes.

For a relubricable unit add "G" suffix after unit number.(Ex. : SAPF 205-16G)