



SBPFL200, SAPFL200 Series

Pressed Steel Oval Flanged Units



Mounted Ball Bearing Units

带冲压座外球面轴承



•SBPFL200

•SAPFL200

SBPFL200 Series, Set Screw Locking

MVB Bearing Unit No.	Shaft Dia d		Dimensions inch mm							Bolt Size		Bearing No.	Housing No.	Weight (kg)	
	(in)	(mm)	a	e	t	b	s	m	Bi	(mm)	(in)				
SBPFL201-8	1/2											M6	1/4	PFL203	0.22
SBPFL202-9	9/16		3.1890	2.5000	0.1575	2.3228	0.2756	0.5512	0.8661						
SBPFL202-10	5/8														
SBPFL203-11	11/16														
SBPFL201		12													
SBPFL202		15	81	63.5	4	59	7	14	22						
SBPFL203		17													
SBPFL204-12	3/4		3.5433	2.8228	0.1575	2.6378	0.3543	0.6614	0.9843			M8	5/16	PFL204	0.26
SBPFL204		20	90	71.7	4	67	9	16.8	25						
SBPFL205-13	13/16											M8	5/16	PFL205	0.35
SBPFL205-14	7/8		3.7402	2.9921	0.1969	2.7953	0.3543	0.8268	1.0630						
SBPFL205-15	15/16														
SBPFL205-16	1														
SBPFL205		25	95	76	5	71	9	21	27						
SBPFL206-17	1-1/16											M10	3/8	PFL206	0.55
SBPFL206-18	1-1/8		4.4488	3.5472	0.1969	3.3071	0.4331	0.7677	1.1811						
SBPFL206-19	1-3/16														
SBPFL206-20	1-1/4														
SBPFL206		30	113	90.1	5	84	11	19.5	30						
SBPFL207-20	1-1/4											M10	3/8	PFL207	0.72
SBPFL207-21	1-5/16		4.8031	3.9370	0.1969	3.7008	0.4331	0.7874	1.2598						
SBPFL207-22	1-3/8														
SBPFL207-23	1-7/16														
SBPFL207		35	122	100	5	94	11	20	32						
SBPFL208-24	1-1/2		5.7874	4.6850	0.2756	4.0945	0.5315	1.1220	1.3386			M12	1/2	PFL208	0.95
SBPFL208-25	1-9/16														
SBPFL208		40	147	119	7	104	13.5	28.5	34						

SAPFL200 Series, Eccentric Collar Locking

MVB Bearing Unit No.	Shaft Dia d		Dimensions inch mm							Bolt Used		Bearing No.	Housing No.	Weight (kg)	
	(in)	(mm)	a	e	t	b	s	m	B	(mm)	(in)				
SAPFL201-8	1/2											M6	1/4	PFL203	0.27
SAPFL202-9	9/16		3.1890	2.5000	0.1575	2.3228	0.2756	0.5512	1.1260						
SAPFL202-10	5/8														
SAPFL203-11	11/16														
SAPFL201		12													
SAPFL202		15	81	63.5	4	59	7	14	28.6						
SAPFL203		17													
SAPFL204-12	3/4		3.5433	2.8228	0.1575	2.6378	0.3543	0.6614	1.2205			M8	5/16	PFL204	0.29
SAPFL204		20	90	71.7	4	67	9	16.8	31						
SAPFL205-13	13/16											M8	5/16	PFL205	0.39
SAPFL205-14	7/8		3.7402	2.9921	0.1969	2.7953	0.3543	0.8268	1.2402						
SAPFL205-15	15/16														
SAPFL205-16	1														
SAPFL205		25	95	76	5	71	9	21	31.5						
SAPFL206-17	1-1/16											M10	3/8	PFL206	0.50
SAPFL206-18	1-1/8		4.4488	3.5472	0.1969	3.3071	0.4331	0.7677	1.4055						
SAPFL206-19	1-3/16														
SAPFL206-20	1-1/4														
SAPFL206		30	113	90.1	5	84	11	19.5	35.7						
SAPFL207-20	1-1/4											M10	3/8	PFL207	0.80
SAPFL207-21	1-5/16		4.8031	3.9370	0.1969	3.7008	0.4331	0.7874	1.5315						
SAPFL207-22	1-3/8														
SAPFL207-23	1-7/16														
SAPFL207		35	122	100	5	94	11	20	38.9						
SAPFL208-24	1-1/2		5.7874	4.6850	0.2756	4.0945	0.5315	1.1220	1.7205			M12	1/2	PFL208	1.01
SAPFL208-25	1-9/16														
SAPFL208		40	147	119	7	104	13.5	28.5	43.7						

Note: For a relubricable unit add "G" suffix after unit number.(Ex. : SAPFL 205-16G)