



MVB Bearing Unit No.	Shaft Dia d		Dimensions(mm)											Bolt Used		Bearing No.	Housing No.	Weight (kg)	
	(in)	(mm)	a	e	i	g	l	s	b	z	Bi	n	(mm)	(in)					
SSUCFL201-8	1/2																SUC201-8		
SSUCFL202-9	9/16																SUC202-9		
SSUCFL202-10	5/8																SUC202-10		
SSUCFL203-11	11/16																SUC203-11		
SSUCFL204-12	3/4																SUC204-12	SFL204	0.51
SSUCFL201		12	113	90	15	11	25.5	12	60	33.3	31	12.7	M10	3/8		SUC201			
SSUCFL202		15														SUC202			
SSUCFL203		17														SUC203			
SSUCFL204		20														SUC204			
SSUCFL205-13	13/16																SUC205-13		
SSUCFL205-14	7/8																SUC205-14		
SSUCFL205-15	15/16																SUC205-15	SFL205	0.6
SSUCFL205-16	1																SUC205-16		
SSUCFL205		25	130	99	16	13	27	16	68	35.7	34.1	14.3	M14	3/8		SUC205			
SSUCFL206-17	1-1/16																SUC206-17		
SSUCFL206-18	1-1/8																SUC206-18		
SSUCFL206-19	1-3/16																SUC206-19	SFL206	0.9
SSUCFL206-20	1-1/4																SUC206-20		
SSUCFL206		30	148	117	18	13	31	16	80	40.2	38.1	15.9	M14	3/8		SUC206			
SSUCFL207-20	1-1/4																SUC207-20		
SSUCFL207-21	1-5/16																SUC207-21		
SSUCFL207-22	1-3/8																SUC207-22	SFL207	1.2
SSUCFL207-23	1-7/16																SUC207-23		
SSUCFL207		35	161	130	19	14	34	16	90	44.4	42.9	17.5	M14	7/16		SUC207			
SSUCFL208-24	1-1/2																SUC208-24		
SSUCFL208-25	1-9/16																SUC208-25		
SSUCFL208		40	175	144	21	14	36	16	100	51.2	49.2	19	M14	1/2		SUC208	SFL208	1.5	
SSUCFL209-26	1-5/8																SUC209-26		
SSUCFL209-27	1-11/16																SUC209-27		
SSUCFL209-28	1-3/4																SUC209-28	SFL209	1.9
SSUCFL209		45	188	148	22	16	38	19	108	52.2	49.2	19	M16	1/2		SUC209			
SSUCFL210-29	1-13/16																SUC210-29		
SSUCFL210-30	1-7/8																SUC210-30		
SSUCFL210-31	1-15/16																SUC210-31	SFL210	2.2
SSUCFL210-32	2																SUC210-32		
SSUCFL210		50	197	157	22	16	40	19	115	54.6	51.6	19	M16	1/2		SUC210			
SSUCFL211-32	2																SUC211-32		
SSUCFL211-33	2-1/16																SUC211-33		
SSUCFL211-34	2-1/8																SUC211-34	SFL211	3
SSUCFL211-35	2-3/16																SUC211-35		
SSUCFL211		55	224	184	25	18	43	19	130	58.4	55.6	22.2	M16	5/8		SUC211			
SSUCFL212-36	2-1/4																SUC212-36		
SSUCFL212-37	2-5/16																SUC212-37		
SSUCFL212-38	2-3/8																SUC212-38	SFL212	4
SSUCFL212-39	2-7/16																SUC212-39		
SSUCFL212		60	250	202	29	18	48	23	140	68.7	65.1	25.4	M20	5/8		SUC212			
SSUCFL213-40	2-1/2																SUC213-40		
SSUCFL213-41	2-9/16																SUC213-41	SFL213	5
SSUCFL213		65	258	210	30	20	50	23	155	69.7	65.1	25.4	M20	5/8		SUC213			
SSUCFL214-42	2-5/8																SUC214-42		
SSUCFL214-43	2-11/16																SUC214-43	SFL214	5.6
SSUCFL214-44	2-3/4																SUC214-44		
SSUCFL214		70	265	216	31	20	54	23	160	75.4	74.6	30.2	M20	5/8		SUC214			
SSUCFL215-45	2-13/16																SUC215-45		
SSUCFL215-46	2-7/8																SUC215-46	SFL215	6.2
SSUCFL215-47	2-15/16																SUC215-47		
SSUCFL215-48	3																SUC215-48		
SSUCFL215		75	275	225	34	22	56	23	165	78.5	77.8	33.3	M20	5/8		SUC215			

NOTE: 1. Grease Fittings available at 90° and 45° positions.

2. Open / Close (OC/CC) Covers are optional.

