



www.mvbbearing.com

标准型 Standard Type ST...	密封型 Sealed Type ST...UU	最大行程 Maximum Stroke mm	钢球圈数 Ball circuit	公称轴径 Nominal shaft dia. mm	主要尺寸和公差 Major dimensions and tolerance(T)										额定负荷 Basic load rating		重量 Weight (g)
					dr	D		L		ℓ	T	t	d	r	动负荷 Dynamic C N	静负荷 Static Co N	
					公差 Tolerance μ m	mm	公差 Tol. μ m	mm	公差 Tol. μ m	mm	mm	mm	mm	mm			
ST6B	-				+22 +13	12	0 -8	19	0 -0.2	11.3	1.1	0.25	-	0.3			
ST8B	ST8BUU	8	6	8	+18 +10	15		24		17.1	1.5	0.5	1.5	0.5	2,060	550	17.6
ST10B	ST10BUU	8	6	10		19	0 -9	30		22.7	1.5	0.5	1.5	0.5	4,610	1,270	34.5
ST12B	ST12BUU	8	6	12	+27 +16	23		32	24.5	1.5	0.5	1.5	0.5	8,140	2,250	53.5	
ST16B	ST16BUU	16	6	16		28		37	29.1	1.5	0.5	1.5	0.5	8,040	2,650	85	
ST20B	ST20BUU	28	6	20		32	0 -11	45	35.8	2	0.5	2	0.5	8,330	3,240	120	
ST25B	ST25BUU	28	6	25	+33 +20	37		45	35.8	2	0.5	2	1	8,140	3,630	142	
ST30B	ST30BUU	44	6	30		45		65	53.5	2.5	0.5	2.5	1	18,700	8,140	275	
ST35B	ST35BUU	54	6	35		52		70	58.5	2.5	0.7	2.5	1.5	18,700	9,020	410	
ST40B	ST40BUU	66	6	40	+41 +25	60	0 -13	80	68.3	2.5	0.7	2.5	1.5	25,000	12,400	635	
ST45B	ST45BUU	66	6	45		65		80	68.3	2.5	0.7	2.5	1.5	25,200	13,500	695	
ST50B	ST50BUU	88	6	50		72		100	86.4	3	1	3	1.5	32,500	17,700	1020	
ST55B	ST55BUU	88	6	55		80		100	86.4	3	1	3	2	33,000	19,300	1380	
ST60B	ST60BUU	88	6	60	+49 +30	85	0 -15	100	86.4	3	1	3	2	33,600	21,000	1,480	
ST70B	ST70BUU	88	6	70		95		100	86.4	3	1	3	2	33,800	23,300	1,670	
ST80B	ST80BUU	76	6	80		110		100	86	3	1.5	3	2	42,500	30,600	2,430	
ST90B	ST90BUU	76	6	90		120		100	86	3	1.5	3	2	43,300	33,700	2,670	
ST100B	ST100BUU	76	6	100	+58 +36	130	0 -18	100	86	3	1.5	3	2	43,900	36,800	2,910	