



MVB Bearing Unit No.	Shaft Dia d		Dimensions (inch / mm)										Bolt Size		Bearing No.	Housing No.	Weight (kg)				
	(in)	(mm)	h	L	e	B	S2	S1	g	w	Bi	n	(in)	(mm)							
UCWAK201-8	1/2												3/8	M10	UCW201-8	AK203	0.62				
UCWAK202-10	5/8																		UCW202-10		
UCWAK203-11	11/16		1.0630	4.7244	3.5039	1.3780	0.6299	0.5118	0.5000	2.1260	1.0787	0.4528							UCW203-11		
UCWAK201		12	27	121	89	35	16	13	12.7	54	27.4	11.5							UCW201		
UCWAK202		15																	UCW202		
UCWAK203		17													UCW203						
UCAK201-8	1/2												3/8	M10	UC201-8	AK204	0.78				
UCAK202-10	5/8																		UC202-10		
UCAK203-11	11/16																		UC203-11		
UCAK204-12	3/4		1.2520	5.2362	3.8583	1.6142	0.6299	0.5118	0.5512	2.4803	1.2205	0.5000							UC204-12		
UCAK201		12	31.8	133	98	41	16	13	14	63	31	12.7							UC201		
UCAK202		15																	UC202		
UCAK203		17																	UC203		
UCAK204		20																	UC204		
UCAK205-13	13/16														3/8			M10	UC205-13	AK205	1.02
UCAK205-14	7/8																				
UCAK205-15	15/16		1.3110	5.5118	4.1339	1.7323	0.6299	0.5118	0.6299	2.6772	1.3425	0.5630				UC205-15					
UCAK205-16	1		33.3	140	105	44	16	13	16	68	34.1	14.3				UC205-16					
UCAK205		25														UC205					
UCAK206-17	1-1/16												7/16	M12	UC206-17	AK206	1.31				
UCAK206-18	1-1/8																		UC206-18		
UCAK206-19	1-3/16		1.5630	6.2992	4.7638	1.8898	0.7480	0.5906	0.6693	3.1496	1.5000	0.6260							UC206-19		
UCAK206-20	1-1/4		39.7	160	121	48	19	15	17	80	38.1	15.9							UC206-20		
UCAK206		30																	UC206		
UCAK207-20	1-1/4												7/16	M12	UC207-20	AK207	1.61				
UCAK207-21	1-5/16																		UC207-21		
UCAK207-22	1-3/8		1.8110	6.5748	5.0000	1.8898	0.7480	0.5906	0.7480	3.6220	1.6890	0.6890							UC207-22		
UCAK207-23	1-7/16		46	167	127	48	19	15	19	92	42.9	17.5							UC207-23		
UCAK207		35																	UC207		
UCAK208-24	1-1/2												7/16	M12	UC208-24	AK208	2.14				
UCAK208-25	1-9/16		1.9370	7.1260	5.5118	2.1260	0.7480	0.5906	0.7480	3.9370	1.9370	0.7480							UC208-25		
UCAK208		40	49.2	181	140	54	19	15	19	100	49.2	19.0							UC208		
UCAK209-26	1-5/8												7/16	M12	UC209-26	AK209	2.5				
UCAK209-27	1-11/16		2.0630	7.4803	5.7480	2.1260	0.7480	0.5906	0.8268	4.1732	1.9370	0.7480							UC209-27		
UCAK209-28	1-3/4		52.4	190	146	54	19	15	21	106	49.2	19.0							UC209-28		
UCAK209		45																	UC209		
UCAK210-29	1-13/16												7/16	M12	UC210-29	AK210	2.95				
UCAK210-30	1-7/8																		UC210-30		
UCAK210-31	1-15/16		2.1890	7.9921	6.2598	2.2441	0.7480	0.5906	0.8661	4.4488	2.0315	0.7480							UC210-31		
UCAK210-32	2		55.6	203	159	57	19	15	22	113	51.6	19.0							UC210-32		
UCAK210		50																	UC210		
UCAK211-32	2												5/8	M16	UC211-32	AK211	3.85				
UCAK211-33	2-1/16																		UC211-33		
UCAK211-34	2-1/8		2.4370	9.1339	7.1260	2.3622	0.9449	0.7874	0.9843	4.9213	2.1890	0.8740							UC211-34		
UCAK211-35	2-3/16		61.9	232	181	60	24	20	25	125	55.6	22.2							UC211-35		
UCAK211		55																	UC211		
UCAK212-36	2-1/4												5/8	M16	UC212-36	AK212	5.1				
UCAK212-37	2-5/16																		UC212-37		
UCAK212-38	2-3/8		2.6890	9.4882	7.5000	2.5197	0.9449	0.7874	1.1417	5.3543	2.5630	1.0000							UC212-38		
UCAK212-39	2-7/16		68.3	241	190.5	64	24	20	29	136	65.1	25.4							UC212-39		
UCAK212		60													UC212						
UCAK213-40	2-1/2												3/4	M20	UC213-40	AK213	6.26				
UCAK213-41	2-9/16		2.6890	9.7638	7.6378	2.7559	1.1417	0.7874	1.0630	5.5512	2.5630	1.0000							UC213-41		
UCAK213		65	68.3	248	194	70	29	20	27	141	65.1	25.4							UC213		
UCAK214-42	2-5/8												3/4	M20	UC214-42	AK214	6.9				
UCAK214-43	2-11/16		3.2520	11.5748	9.1339	2.8346	1.2598	0.7874	1.1417	6.2992	2.9370	1.1890							UC214-43		
UCAK214-44	2-3/4		82.6	294	232	72	32	20	29	160	74.6	30.2							UC214-44		
UCAK214		70																	UC214		
UCAK215-45	2-13/16												3/4	M20	UC215-45	AK215	7.62				
UCAK215-46	2-7/8																		UC215-46		
UCAK215-47	2-15/16		3.3110	11.9685	9.4882	2.9134	1.2598	0.8661	1.2598	6.4961	3.0630	1.3110							UC215-47		
UCAK215-48	3		84.1	304	241	74	32	22	32	165	77.8	33.3							UC215-48		
UCAK215		75																	UC215		

NOTE: 1. Grease Fittings available at 90° and 45° positions.

2. Open / Close (S/SM) Covers are optional.