



S/SM-UCFL

MVB Bearing Unit No.	Shaft Dia d		Dimensions(mm)											Bolt Size	Bearing No.	Housing No.	Weight (kg)
	(in)	(mm)	a	e	i	g	l	s	b	t	z	Bi	n				
UCWFL201-8 UCWFL202-9 UCWFL202-10 UCWFL203-11 UCWFL201 UCWFL202 UCWFL203	1/2 9/16 5/8 11/16	12 15 17	3 8/9	3	19/32	7/16	15/16	7/16	2 1/4	1 31/64	1 1/4	1.0236	0.393701	3/8	UCW201-8 UCW202-9 UCW202-10 UCW203-11 UCW201 UCW202 UCW203	FL203	0.52
UCFL201-8 UCFL202-9 UCFL202-10 UCFL203-11 UCFL204-12 UCFL201 UCFL202 UCFL203 UCFL204	1/2 9/16 5/8 11/16 3/4	12 15 17 20	4 7/16	3 35/64	19/32	7/16	1	15/32	2 3/8	1 31/64	1 5/16	1.2205	0.5	3/8	UC201-8 UC202-9 UC202-10 UC203-11 UC204-12 UC201 UC202 UC203 UC204	FL204	0.51
UCFL205-13 UCFL205-14 UCFL205-15 UCFL205-16 UCFL205	13/16 7/8 15/16 1	25	5 1/8	3 57/64	5/8	1/2	1 1/16	5/8	2 11/16	1 9/16	1 13/32	1.3386	0.563	1/2	UC205-13 UC205-14 UC205-15 UC205-16 UC205	FL205	0.6
UCFL206-17 UCFL206-18 UCFL206-19 UCFL206-20 UCFL206	1-1/16 1-1/8 1-3/16 1-1/4	30	5 13/16	4 39/64	45/64	1/2	1 7/32	5/6	3 5/32	1 3/4	1 19/32	1.5	0.626	1/2	UC206-17 UC206-18 UC206-19 UC206-20 UC206	FL206	0.9
UCFL207-20 UCFL207-21 UCFL207-22 UCFL207-23 UCFL207	1-1/4 1-5/16 1-3/8 1-7/16	35	6 11/32	5 1/8	3/4	9/16	1 11/32	5/8	3 17/32	1 29/32	1 3/4	1.689	0.689	1/2	UC207-20 UC207-21 UC207-22 UC207-23 UC207	FL207	1.2
UCFL208-24 UCFL208-25 UCFL208	1-1/2 1-9/16	40	6 7/8	5 43/64	53/64	9/16	1 13/32	5/8	3 15/16	2 3/16	2 1/32	1.937	0.748	1/2	UC208-24 UC208-25 UC208	FL208	1.5
UCFL209-26 UCFL209-27 UCFL209-28 UCFL209	1-5/8 1-11/16 1-3/4	45	7 13/32	5 53/64	55/64	19/32	1 1/2	3/4	4 1/4	2 1/16	2 1/16	1.937	0.748	5/8	UC209-26 UC209-27 UC209-28 UC209	FL209	1.9
UCFL210-29 UCFL210-30 UCFL210-31 UCFL210-32 UCFL210	1-13/16 1-7/8 1-15/16 2	50	7 3/4	6 3/16	55/64	19/32	1 9/16	3/4	4 17/32	2 11/32	2 5/32	2.0315	0.748	5/8	UC210-29 UC210-30 UC210-31 UC210-32 UC210	FL210	2.2
UCFL211-32 UCFL211-33 UCFL211-34 UCFL211-35 UCFL211	2 2-1/16 2-1/8 2-3/16	55	8 13/16	7 1/4	63/64	23/32	1 11/16	3/4	5 1/8	2 31/64	2 5/16	2.189	0.874	5/8	UC211-32 UC211-33 UC211-34 UC211-35 UC211	FL211	3
UCFL212-36 UCFL212-37 UCFL212-38 UCFL212-39 UCFL212	2-1/4 2-5/16 2-3/8 2-7/16	60	9 27/32	7 61/64	1 9/64	23/32	1 7/8	29/32	5 1/2	2 57/64	2 23/32	2.563	1	3/4	UC212-36 UC212-37 UC212-38 UC212-39 UC212	FL212	4
UCFL213-40 UCFL213-41 UCFL213	2-1/2 2-9/16	65	10 5/32	8 17/64	1 3/16	25/32	1 31/32	29/32	6 3/32	2 15/16	2 3/4	2.563	1	3/4	UC213-40 UC213-41 UC213	FL213	5
UCFL214-42 UCFL214-43 UCFL214-44 UCFL214	2-5/8 2-11/16 2-3/4	70	10 7/16	8 1/2	1 7/32	25/32	2 1/8	29/32	6 5/16	3 13/64	2 31/32	2.937	1.189	3/4	UC214-42 UC214-43 UC214-44 UC214	FL214	5.6
UCFL215-45 UCFL215-46 UCFL215-47 UCFL215-48 UCFL215	2-13/16 2-7/8 2-15/16 3	75	10 13/16	8 55/64	1 11/32	25/32	2 7/32	29/32	6 1/2	3 9/32	3 3/32	3.063	1.311	3/4	UC215-45 UC215-46 UC215-47 UC215-48 UC215	FL215	6.2
UCFL216-50 UCFL216	3-1/8	80	11 13/32	9 11/64	1 11/32	25/32	2 9/32	63/64	7 3/32	3 39/64	3 9/32	2.252	1.311	7/8	UC216-50 UC216	FL216	7.8
UCFL217-52 UCFL217	3-1/4	85	12 9/49	9 49/64	1 27/64	7/8	2 15/32	63/64	7 15/32	3 41/64	3 7/16	3.374	1.3425	7/8	UC217-52 UC217	FL217	9.8
UCFL218-56 UCFL218	3-1/2	90	12 19/32	10 7/16	1 37/64	29/32	2 11/16	63/64	8 1/16	4	3 25/32	3.7795	1.563	7/8	UC218-56 UC218	FL218	12.4

NOTE: 1. Grease Fittings available at 90° and 45° positions.

2. Open / Close (S/SM) Covers are optional.