



MVB Bearing Unit No.	Shaft Dia d		Dimensions (inch) / (mm)										Bolt Size		Bearing No.	Housing No.	Housing Weight (kg)
	(in)	(mm)	h	a	e	b	c	g	w	s	Bi	n	(mm)	(in)			
UCSB205-13	13/16												M10	3/8	UC205-13	SB205	0.65
UCSB205-14	7/8		1.2480	3.6220	2.7559	1.4961	0.9843	2.2835	2.6260	0.4331	1.3425	0.5630			UC205-14		
UCSB205-15	15/16														UC205-15		
UCSB205-16	1														UC205-16		
UCSB205		25	31.7	92	70	38	25	58	66.7	11	34.1	14.3			UC205		
UCSB206-17	1-1/16												M10	3/8	UC206-17	SB206	0.72
UCSB206-18	1-1/8		1.5000	4.2520	3.2677	1.7323	1.1811	2.6772	3.0748	0.4331	1.5000	0.6260			UC206-18		
UCSB206-19	1-3/16														UC206-19		
UCSB206-20	1-1/4														UC206-20		
UCSB206		30	38.1	108	83	44	30	68	78.1	11	38.1	15.9			UC206		
UCSB207-20	1-1/4												M12	7/16	UC207-20	SB207	0.75
UCSB207-21	1-5/16		1.7480	5.2362	4.0157	1.8898	1.2992	2.9921	3.7165	0.5512	1.6890	0.6890			UC207-21		
UCSB207-22	1-3/8														UC207-22		
UCSB207-23	1-7/16														UC207-23		
UCSB207		35	44.4	133	102	48	33	76	94.4	14	42.9	17.5			UC207		
UCSB208-24	1-1/2												M12	7/16	UC208-24	SB208	1.75
UCSB208-25	1-9/16		1.8740	5.5118	4.2520	2.1260	1.5354	3.1890	3.9224	0.5512	1.9370	0.7480			UC208-25		
UCSB208		40	47.6	140	108	54	39	81	99.63	14	49.2	19			UC208		
UCSB209-26	1-5/8												M12	7/16	UC209-26	SB209	2.2
UCSB209-27	1-11/16		2.0000	5.7480	4.3701	2.1260	1.5354	3.3858	4.1260	0.5512	1.9370	0.7480			UC209-27		
UCSB209-28	1-3/4														UC209-28		
UCSB209		45	50.8	146	111	54	39	86	104.8	14	49.2	19			UC209		
UCSB210-29	1-13/16												M12	7/16	UC210-29	SB210	2.4
UCSB210-30	1-7/8		2.1260	5.9843	4.6457	2.3622	1.6142	3.5433	4.3295	0.5512	2.0315	0.7480			UC210-30		
UCSB210-31	1-15/16														UC210-31		
UCSB210-32	2														UC210-32		
UCSB210		50	54	152	118	60	41	90	109.97	14	51.6	19			UC210		
UCSB211-32	2												M16	5/8	UC211-32	SB211	3.3
UCSB211-33	2-1/16		2.3110	6.7717	5.3937	2.3622	1.6142	3.8583	4.7929	0.7087	2.1890	0.8740			UC211-33		
UCSB211-34	2-1/8														UC211-34		
UCSB211-35	2-13/16														UC211-35		
UCSB211		55	58.7	172	137	60	41	98	121.74	18	55.6	22.2			UC211		
UCSB212-36	2-1/4												M16	5/8	UC212-36	SB212	5
UCSB212-37	2-5/16		2.7520	7.7559	6.3780	2.5591	1.8898	4.3701	5.7480	0.6693	2.5630	1.0000			UC212-37		
UCSB212-38	2-3/8														UC212-38		
UCSB212-39	2-7/16														UC212-39		
UCSB212		60	69.9	197	162	65	48	111	146	17	65.1	25.4	UC212				
UCSB213-40	2-1/2												M16	5/8	UC213-40	SB213	4.5
UCSB213-41	2-9/16		2.7520	7.7559	6.3780	2.5591	1.8898	4.3701	5.7480	0.6693	2.5630	1.0000			UC213-41		
UCSB213		65	69.9	197	162	65	48	111	146	17	65.1	25.4			UC213		
UCSB214-42	2-5/8												M16	5/8	UC214-42	SB214	6
UCSB214-43	2-11/16		3.0000	8.1102	6.7717	2.8740	2.3622	4.6063	6.1024	0.6693	2.9370	1.1890			UC214-43		
UCSB214-44	2-3/4														UC214-44		
UCSB214		70	76.2	206	172	73	60	117	155	17	74.6	30.2			UC214		
UCSB215-45	2-13/16												M16	5/8	UC215-45	SB215	5.74
UCSB215-46	2-7/8		3.0000	8.1102	6.7717	2.8740	2.3622	4.6063	6.1024	0.6693	3.0630	1.3110			UC215-46		
UCSB215-47	2-15/16														UC215-47		
UCSB215-48	3														UC215-48		
UCSB215		75	76.2	206	172	73	60	117	155	17	77.8	33.3	UC215				
UCSB216-50	3-1/8												M20	3/4	UC216-50	SB216	7.76
UCSB216		80	82.6	238	191	86	64	127	168	21	82.6	33.3			UC216		
UCSB217-52	3-1/4												M20	3/4	UC217-52	SB217	9.64
UCSB217		85	88.9	254	203	89	64	136	181	21	85.7	34.1			UC217		
UCSB218-56	3-1/2												M24		UC218-56	SB218	11.83
UCSB218		90	98.4	273	222	92	67	152	200	25	96	39.7			UC218		
UCSBX20-63	3-15/16												M24		UCX20-63	SBX20	17.4
UCSBX20-64	4		4.2520	11.7323	9.4882	4.2520	2.7559	7.0079	8.7008	1.0236	4.6260	1.9370			UCX20-64		
UCSBX20		100	108	298	241	108	70	178	221	26	117.5	49.2			UCX20		

NOTE: 1. Grease Fittings available at 90° and 45° positions.