



MVB Bearing Unit No.	Shaft Dia		Dimension (in) (mm)											Bolt Used		Bearing No.	Housing No.	Weight Kg
	d (in)	d (mm)	h	a	e	b	S2	S1	g	w	c	Bi	n	(mm)	(in)			
UCSL201 UCSL201-8	1/2	12	1 1/16 27	4 3/4 121	3 1/2 89	1 1/8 29	5/8 16	7/16 11	1/2 13	2 3/16 56	7/8 22	1.0648 26.59	0.4374 11.11	8	3/8	UC201 UC201-8	SL03	0.53
UCSL202 UCSL202-9 UCSL202-10	9/16 5/8	15	1 1/16 27	4 3/4 121	3 1/2 89	1 1/8 29	5/8 16	7/16 11	1/2 13	2 3/16 56	7/8 22	1.0468 26.59	0.4374 11.11	8	3/8	UC202 UC202-9 UC202-10	SL03	0.53
UCSL203 UCSL203-11		17	1 1/16 27	4 3/4 121	3 1/2 89	1 1/8 29	5/8 16	7/16 11	1/2 13	2 3/16 56	7/8 22	1.0468 26.59	0.4374 11.11	8	3/8	UC203-11	SL03	0.53
UCSL204-12 UCSL204	3/4	20	1 1/4 31.8	5 1/4 133	3 7/8 98	1 1/4 32	3/4 19	7/16 11	1/2 13	2 15/32 62.8	1 25	1.2205 31	0.5 12.7	8	3/8	UC204-12 UC204	SL04	0.73
UCSL205-13 UCSL205-14 UCSL205-15 UCSL205 UCSL205-16	13/16 7/8 15/16 1	25	1 5/16 33.3	5 1/2 140	4 1/8 105	1 1/2 38	3/4 19	7/16 11	5/8 16	2 21/32 67.8	1 25	1.3386 34	0.563 14.3	8	3/8	UC205-13 UC205-14 UC205-15 UC205 UC205-16	SL05	0.95
UCSL206-17 UCSL206-18 UCSL206 UCSL206-19 UCSL206-20	1 1/16 1 1/8 1 3/16 1 1/4	30	1 9/16 39.7	6 1/2 165	4 7/8 124	1 5/8 41	7/8 22	9/16 14	11/16 17.5	3 3/16 81	1 3/16 30	1.5 38.1	0.626 15.9	12	1/2	UC206-17 UC206-18 UC206 UC206-19 UC206-20	SL06	1.3
UCSL207-20 UCSL207-21 UCSL207-22 UCSL207 UCSL207-23	1 1/4 1 5/16 1 3/8 1 7/16	35	1 13/16 46	7 178	5 3/8 136.5	1 7/8 48	7/8 22	9/16 14	3/4 19	3 19/32 91.5	1 1/4 32	1.689 42.9	0.689 17.5	12	1/2	UC207-20 UC207-21 UC207-22 UC207 UC207-23	SL07	1.9
UCSL208-24 UCSL208-25 UCSL208	1 1/2 1 9/16	40	1 15/16 49.2	7 1/4 184	5 5/8 143	2 51	7/8 22	9/16 14	13/16 21	3 15/16 100	1 5/16 33	1.937 49.2	0.748 19	12	1/2	UC208-24 UC208-25 UC208	SL08	2.2
UCSL209-26 UCSL209-27 UCSL209-28 UCSL209	1 5/8 1 11/16 1 3/4	45	2 1/16 52.4	7 3/4 197	6 152	2 1/8 54	1 26	9/16 14	13/16 21	4 1/8 104.4	1 5/16 33.5	1.937 49.2	0.748 19	12	1/2	UC209-26 UC209-27 UC209-28 UC209	SL09	2.8
UCSL210-30 UCSL210-31 UCSL210	1 7/8 1 15/16	50	2 3/16 55.6	8 3/8 213	6 1/2 165	2 1/4 57	1 26	9/16 14	7/8 22	4 7/16 113	1 7/16 37	2.0315 51.6	0.748 19	12	1/2	UC210-30 UC210-31 UC210	SL10	3.1
UCSL211-32 UCSL211-34 UCSL211 UCSL211-35	2 2 1/8 2 3/16	55	2 7/16 61.9	9 1/4 235	7 1/4 184	2 1/2 64	1 1/8 29	11/16 17	1 25	4 27/32 123.4	1 17/32 39	2.189 55.6	0.874 22.2	14	5/8	UC211-32 UC211-34 UC211 UC211-35	SL11	4.1
UCSL212-36 UCSL212 UCSL212-38 UCSL212-39	2 1/4 2 3/8 2 7/16	60	2 11/16 68.3	9 3/4 248	7 5/8 194	2 3/4 70	1 1/8 29	11/16 17	1 1/8 29	5 7/16 138	1 13/16 46	2.563 65.1	1 25.4	14	5/8	UC212-36 UC212 UC212-38 UC212-39	SL12	5.3
UCSL213-40 UCSL213	2 1/2	65	2 11/16 68.3	9 3/4 248	7 5/8 194	2 3/4 70	1 1/8 29	11/16 17	1 1/8 29	5 7/8 143	1 13/16 46	2.563 65.1	1 25.4	14	5/8	UC213-40 UC213	SL13	6.4
UCSL214-44 UCSL214	2 3/4	70	3 1/4 82.6	11 3/4 298	9 1/8 232	3 1/4 82	1 1/4 32	13/16 21	1 5/16 33	6 5/16 160	1 31/32 50	2.937 74.6	1.189 30.2	18	3/4	UC214-44 UC214	SL14	7.6
UCSL215 UCSL215-48	3	75	3 1/4 82.6	11 3/4 298	9 1/8 232	3 1/4 82	1 1/4 32	13/16 21	1 5/16 33	6 13/32 163	1 31/32 50	3.063 77.8	1.311 33.3	18	3/4	UC215 UC215-48	SL15	9.4

NOTE: 1. Grease Fittings available at 90° and 45° positions.