



UCX00L3 (Medium Duty)
Spherical O.D.



CUCX00L3 (Medium Duty)
Cylindrical O.D.



UC200G-L3 (Medium Duty)
Relubricatable Type



L3 TYPE SEAL

www.mvbbearing.com

MVB Bearing No.		Shaft Dia d		Dimensions (inch / mm)									Basic Load Ratings (KN)		Weight (kg)	
Spherical Out Ring	Cylindrical Out Ring	(in)	(mm)	D	Bi	Be	r	n	m	G	ds(in.)/(mm)	F	Dynamic Cr	Static Cor		
UCX05-13	CUCX05-13	13/16														0.39
UCX05-14	CUCX05-14	7/8		2.4409	1.5000	0.7480	0.0591	0.6260	0.8740	0.1969	1/4-28UNF	0.19685	14.97	10.04	0.38	
UCX05-15	CUCX05-15	15/16													0.36	
UCX05-16	CUCX05-16	1													0.34	
UCX05	CUCX05		25	62	38.1	19	1.5	15.9	22.2	5	M6x1	5			0.35	
UCX06-17	CUCX06-17	1-1/16													0.59	
UCX06-18	CUCX06-18	1-1/8		2.8346	1.6890	0.7874	0.0787	0.6890	1.0000	0.2362	5/16-24UNF	0.224409	19.75	13.67	0.57	
UCX06-19	CUCX06-19	1-3/16													0.54	
UCX06-20	CUCX06-20	1-1/4													0.52	
UCX06	CUCX06		30	72	42.9	20	2	17.5	25.4	6	M8x1	5.7			0.54	
UCX07-20	CUCX07-20	1-1/4													0.77	
UCX07-21	CUCX07-21	1-5/16		3.1496	1.9370	0.8268	0.0787	0.7480	1.1890	0.3150	5/16-24UNF	0.244094	22.71	15.94	0.74	
UCX07-22	CUCX07-22	1-3/8													0.7	
UCX07-23	CUCX07-23	1-7/16													0.67	
UCX07	CUCX07		35	80	49.2	21	2	19	30.2	8	M8x1	6.2			0.7	
UCX08-24	CUCX08-24	1-1/2													0.92	
UCX08-25	CUCX08-25	1-9/16		3.3465	1.9370	0.8661	0.0787	0.7480	1.1890	0.3150	5/16-24UNF	0.251969	24.36	17.71	0.88	
UCX08	CUCX08		40	85	49.2	22	2	19	30.2	8	M8x1	6.4			0.88	
UCX09-26	CUCX09-26	1-5/8													1.13	
UCX09-27	CUCX09-27	1-11/16		3.5433	2.0315	0.9449	0.0787	0.7480	1.2835	0.3937	3/8-24UNF	0.255906	26.98	19.84	1.09	
UCX09-28	CUCX09-28	1-3/4													1.05	
UCX09	CUCX09		45	90	51.6	24	2	19	32.6	10	M10x1.25	6.5			1.03	
UCX10-29	CUCX10-29	1-13/16													1.14	
UCX10-30	CUCX10-30	1-7/8		3.9370	2.1890	0.9843	0.0984	0.8740	1.3150	0.3937	3/8-24UNF	0.275591	33.37	25.11	1.36	
UCX10-31	CUCX10-31	1-15/16													1.31	
UCX10-32	CUCX10-32	2													1.26	
UCX10	CUCX10		50	100	55.6	25	2.5	22.2	33.4	10	M10x1.25	7			1.28	
UCX11-32	CUCX11-32	2													1.9	
UCX11-33	CUCX11-33	2-1/16		4.3307	2.5630	1.0630	0.0984	1.0000	1.5630	0.3937	3/8-24UNF	0.299213	36.74	27.97	1.84	
UCX11-34	CUCX11-34	2-1/8													1.77	
UCX11-35	CUCX11-35	2-3/16													1.7	
UCX11	CUCX11		55	110	65.1	27	2.5	25.4	39.7	10	M10x1.25	7.6			1.73	
UCX12-36	CUCX12-36	2-1/4													2	
UCX12-37	CUCX12-37	2-5/16		4.7244	2.5630	1.1024	0.0984	1.0000	1.5630	0.3937	3/8-24UNF	0.334646	44.01	34.18	1.93	
UCX12-38	CUCX12-38	2-3/8													1.85	
UCX12-39	CUCX12-39	2-7/16													1.78	
UCX12	CUCX12		60	120	65.1	28	2.5	25.4	39.7	10	M10x1.25	8.5			1.87	
UCX13-40	CUCX13-40	2-1/2		4.9213	2.9370	1.1811	0.0984	1.1890	1.7480	0.4724	7/16-20UNF	0.350394	46.79	37.59	2.32	
UCX13-41	CUCX13-41	2-9/16													2.23	
UCX13	CUCX13		65	125	74.6	30	2.5	30.2	44.4	12	M12x1.5	8.9			2.23	
UCX14-42	CUCX14-42	2-5/8													2.61	
UCX14-43	CUCX14-43	2-11/16		5.1181	3.0630	1.2598	0.0984	1.3110	1.7520	0.4724	7/16-20UNF	0.362205	50.85	41.26	2.5	
UCX14-44	CUCX14-44	2-3/4													2.4	
UCX14	CUCX14		70	130	77.8	32	2.5	33.3	44.5	12	M12x1.5	9.2			2.39	
UCX15-45	CUCX15-45	2-13/16													3.59	
UCX15-46	CUCX15-46	2-7/8		5.5118	3.2520	1.2992	0.1181	1.3110	1.9409	0.5512	7/16-20UNF	0.3780	55.04	45.09	3.47	
UCX15-47	CUCX15-47	2-15/16													3.36	
UCX15-48	CUCX15-48	3													3.23	
UCX15	CUCX15		75	140	82.6	33	3	33.3	49.3	14	M12x1.5	9.6			3.33	
UCX16-50	CUCX16-50	3-1/8		5.9055	3.3740	1.3780	0.1181	1.3425	2.0315	0.5512	7/16-20UNF	0.401575	64.01	53.28	4.16	
UCX16	CUCX16		80	150	85.7	35	3	34.1	51.6	14	M12x1.5	10.2			4.11	
UCX17-52	CUCX17-52	3-1/4		6.2992	3.7795	1.4567	0.1181	1.5630	2.2165	0.5906	7/16-20UNF	0.440945	73.83	60.76	5.01	
UCX17-55	CUCX17-55	3-7/16													4.82	
UCX17	CUCX17		85	160	96	37	3	39.7	56.3	15	M12x1.5	11.2			4.77	
UCX18-56	CUCX18-56	3-1/2		6.6929	4.0945	1.4961	0.1181	1.6890	2.4055	0.5512	1/2-20UNF	0.476378	12.36	84.49	5.5	
UCX18	CUCX18		90	170	104	38	3	42.9	61.1	14	M14x1.5	12.1			5.6	
UCX20-63	CUCX20-63	3-15/16		7.4803	4.6260	1.6535	0.1378	1.9370	2.6890	0.6299	5/8-18UNF	0.519685	14.87	10.71	9	
UCX20-64	CUCX20-64	4													9.1	
UCX20	CUCX20		100	190	117.5	42	3.5	49.2	68.3	16	M16x1.5	13.2			9.2	